

GREEN POOL CLEAN UP PROCEDURE – 40,000LTS – 60,000LTS POOLS



Choose a Visual Appearance Level to Determine Treatment.

Level No.1 Low Level Algae Infestation

Level No.2 Medium Algae Infestation

Level No.3 High Algae Infestation

Below you will find a general guide for a Green Pool Clean Up.

Stage 1 – CLEAN & TREATMENT

1. Using a garden hose, fill pool (connect a tap timer to avoid overflowing)
2. Switch on Filter Pump.
3. Level No.1 – Add 5.0L of Hydrochloric Acid – Add 15L to 30L of Liquid Chlorine – Add 1L of Algae Eliminator – Add 1L of Nil-phos Phosphate Remover.

Level No.2 - Add 7.5L of Hydrochloric Acid – Add 30L to 45L of Liquid Chlorine – Add 1L of Algae Eliminator – Add 1L of Nil-phos Phosphate Remover.

Level No.3 - Add 10L of Hydrochloric Acid – Add 45L to 60L of Liquid Chlorine – Add 1L of Algae Eliminator – Add 1L of Nil-phos Phosphate Remover.

4. Criss-cross the pool, scooping with a leaf rake until no debris remains on the floor.
5. Brush the walls and floor with pool broom.
6. Vacuum pool to waste.
7. For non-vinyl pool only, sprinkle 2.0 KG per 50,000LTS of Granular Chlorine over pool surface to treat algae pool floor. DO NOT SPRINKLE GRANULAR CHLORINE ON VINYL POOLS.
8. Set Tap Timer to fill pool if required.



EITHER / OR STAGE

If pool has turned from green to a white cloudy colour with zero green tones at the end of stage 1, proceed to Stage 2.

If pool has not turned from green to white cloudy colour at the end of the first stage, allow the pump to run until the green colour has been replaced with a white cloudy appearance.

Stage 2 – Floccing *

*** Requires a waste line.**

1. Raise the total alkalinity to 150ppm by adding Buffer (4kg buffer raises 50,000LTS by 50ppm) – Run pump for 10 Minutes to Mix the Buffer into the water.
2. SWITCH OFF ALL PUMPS Including Solar Pump and ensure they are not turned back on during this stage.
3. If you can EASILY see the bottom of the deep end - add 1.0L of FAST FLOC.
if you can not easily see the bottom of the deep end – add 2.0L of FAST FLOC.
If you can see less than 1.0m through the water – add 3.0L of FAST FLOC.
If you can see Less than 0.5m through the water – add 4.0L of FAST FLOC.

Mix Fast-Floc in 6 buckets of pool water and sprinkle evenly over pool surface – Wait 24 Hours with Pump Off.



Stage 3 – Vacuuming to waste – 24 Hours after Floc is added.

1. If you cannot see the bottom, vacuum to waste and repeat stage 2.
2. If you can see the bottom, vacuum to waste.
3. Return the following day to vacuum to waste again if necessary.

Stage 4 – Final Clean

1. If you can see the bottom after Stage 3, switch on filter pump and operate 24 hours per day until clear.

Final Stage – Balance Pool Water & Treat.

1. Balance water & add stabilizer if required.
2. Add 500ml of Winteriser.
3. Add a Pool Clarifier.
4. Ensure Equipment is working as it should.